

Data Sheet

Remote Control

T70 1 ATEX Transmitter

The T70 1 ATEX is highly customizable with many features and accessories. From removable EEPROM SIM module to tandem system solutions, the T70 1 ATEX brings quality and reliability to lifting applications.

Features

- High-sensitivity two-step push button
- Multi-band Radio with Full-Duplex communication
- External removable EEPROM SIM module
- Frequency management against interferences

Benefits

- Highly customizable
- Easy and fast maintenance
- High resistance to impacts
- Intrinsically safe

Applications

- ATEX certified for hazardous applications
- Used in crane applications

Comprehensive technical literature is
online at www.danfoss.com





Technical data

Specification	Value
Stop function	Cat. 3-PLd
Ingress Protection	IP65/NEMA4
Anti-condensation system	N/A
Frequency band	Multi-band (400-930 MHz)
Main mechanisms	Push button (6 total)
Auxiliary mechanisms	Toggle and rotary switches
Removable EEPROM	External
Battery model	BT06K ATEX
Battery life	8h
Operating temperature	-20° to 70° C (-4° to 158° F)
Weight (with battery)	500 g
Harness	Hand/shoulder strap
Display	N/A
Cable connection	N/A
Range limiter	N/A
Associated receivers	R13, R70, MPCAN, R70 ATEX Z1, R13 ATEX Z2

ATEX / IECEx

Ex II 2 GD
 Ex ia IIC T4 Gb
 Ex ia IIIC T135°C Db
 CE0080
 INERIS 08ATEX0006
 IECEx INE 09.0014

CSA / UL

Class I, Division 1, Groups A, B, C & D
 Class II, Division 1, Groups E, F & G
 Zone 21, AEx iaD T135°C T4 IP65

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.